

## CLAIMS

1. A system for protecting sensitive information in a network, comprising:  
5 a network component for storing the sensitive information; and  
a network device, attachable to the network, that lacks the sensitive  
information and is inoperative, at least in part, until the sensitive information is stored  
therein;  
wherein when the network device is attached to the network, the sensitive  
10 information is downloaded from the network component and stored in the network device  
so that device becomes operational;  
wherein when the network device is disconnected from the network, the  
sensitive information is erased from the network device, whereby making the device  
inoperative at least in part and removing the sensitive information from the device.
- 15 2. The system of claim 1, wherein the sensitive information is selected from  
the group consisting of configuration information, a software image, and a combination  
of the forgoing.
3. The system of claim 2, wherein the configuration information is selected  
from the group consisting of a password, a user ID, a network security key, and any  
20 combination of the forgoing.
4. The system of claim 1, wherein the network device includes a volatile  
memory for storing the sensitive information.
5. The system of claim 1, wherein the network component is a LAN switch.
6. The system of claim 1, wherein the network device is a wireless access point  
25 (AP).
7. The system of claim 1, wherein the network component is located in a  
secure environment.
8. A method for protecting sensitive information in a network, comprising:  
storing the sensitive information at a network component;

attaching a network device to the network, the network device lacking the sensitive information and being inoperative, at least in part, until the sensitive information is stored therein;

5        downloading the sensitive information from the network component to the network device;

      storing the sensitive information in the network device so that device becomes operational on the network; and

      when the device is disconnected from the network, erasing the sensitive information from the network device.

10        9.     The method of claim 8, wherein the sensitive information is selected from the group consisting of configuration information, a software image, and a combination of the forgoing.

      10.    The method of claim 9, wherein the configuration information is selected from the group consisting of a password, a user ID, a network security key, and any  
15    combination of the forgoing.

      11.    The method of claim 8 wherein the network device includes a volatile memory for storing the sensitive information.

      12.    The method of claim 8, wherein the network component is a LAN switch.

      13.    The method of claim 8, wherein the network device is a wireless access  
20    point (AP).

      14.    The method of claim 8, wherein the network component is located in a secure environment.

      15.    A device that is non-operational on a network unless the device is storing configuration information, comprising:

25        an interface for communicating with the network;

      a memory whose contents are erased upon loss of power to the device; and

      means for downloading from the network and storing in the memory the configuration information, wherein the configuration information, when stored in the memory, permits the device to operate on the network.

30        16.    The device of claim 15, wherein the downloading means includes:

a bootstrap program for downloading from the network an executable image.

17. The device of claim 16, wherein the executable image permits the device to download the configuration information.

18. The device of claim 16, further comprising means for storing the  
5 executable image in the memory.

19. The device of claim 15, wherein the device is a wireless access point (AP).

20. The device of claim 19, wherein the configuration information includes security information for allowing end user devices to access the network through the wireless AP.

10 21. The device of claim 15, wherein the configuration information includes security information for allowing the device access to the network.

22. A network system, comprising:

a switch for attaching a device to the network so that information can be communicated between the device and the network system, wherein the device is not  
15 fully operational when first connected to the switch; and

means for downloading configuration information from the network system to a volatile memory included in the device in response to a request from the device, the device being operable on the network after the configuration information is downloaded into the volatile memory.

20 23. The network system of claim 22, further comprising:

means for downloading an executable image from the network system to the device.

24. The network system of claim 23, wherein the request is generated by running the executable image on the device.

25 25. The network system of claim 22, wherein the device is a wireless access point (AP).

26. The network system of claim 23, wherein the configuration information includes security information for allowing end user devices to access the network system through the wireless AP.

27. The network system of claim 22, wherein the configuration information includes security information for allowing the device access to the network.

28. The network system of claim 22, further comprising means for authenticating the device on the network.

5 29. A system, comprising:  
a device including

a network interface,

a memory whose contents are erased upon loss of power to the device, and

10 a bootstrap program for downloading and storing an executable image in the memory; and

a network including

15 a port for connecting to the network interface so that information can be communicated between the device and the network, wherein the device is not fully operational when first connected to the port, and

means for downloading the executable image from the network into the memory in response to a request from the bootstrap program, and

20 means for downloading configuration information from the network to the memory in response to a request generated by running the executable image at the device, the device being operational on the network after the configuration information is downloaded into the memory.

30. The system of claim 29, wherein the device is a wireless access point (AP).

25 31. The system of claim 30, wherein the configuration information includes security information for allowing end user devices to access the network through the wireless AP.

32. The system of claim 29, wherein the configuration information includes security information for allowing the device access to the network.

33. The system of claim 29, wherein the network further comprises means for authenticating the device on the network.

34. A method for operating a device on a network, comprising:

attaching the device to the network so that information can be  
5 communicated between the device and the network;

downloading an executable image from the network to the device;

executing the downloaded executable image at the device to obtain  
configuration information from the network; and

10 storing the configuration information in a volatile memory included in the  
device, the device being operable on the network after the configuration  
information is downloaded to the volatile memory, wherein the contents of the  
volatile memory are lost when the device is de-powered.

35. The method of claim 34, wherein the device is a wireless access point  
(AP).

15 36. The method of claim 35, wherein the configuration information includes  
security information for allowing end user devices to access the network through the  
wireless AP.

37. The method of claim 34, wherein the configuration information includes  
security information for allowing the device access to the network.

20 38. The method of claim 34, further comprising:  
authenticating the device on the network.